

LED4DFCAC-W-2PK

LED Candle Replacement Lamps

SKU # 93142797



SPECIFICATIONS

Bulb Base Type Voltage Voltage Wattage Wattage Replacement Operating Life Operating Life Operating Temp Operating Temp Warranty OPERATION Warranty OPERATION WELLIAM OPERATION OPERATION WELLIAM OPERATION OPERATION OPERATION WELLIAM OPERATION OPERATION WELLIAM OPERATION OP	GENERAL		
120	Bulb Shape		CA
Wattage 3.5 W Wattage Replacement 40 Operating Life 15,000 hr Dimmable Yes Operating Temp -20 to 40 °C Warranty 3 year limited warranty PHOTOMETRIC Efficacy 86 LPW Lumens 300 lm CCT 2700 K CRI 80 CRI CRITICATIONS ANTINGS & CERTIFICATIONS Safety Certifications	Bulb Base Type		E12
Watage Replacement Operating Life Operating Life Dimmable Operating Temp Operati	Voltage		120
Operating Life 15,000 hr Dimmable Yes Operating Temp -20 to 40 °C Warranty 3 year limited warranty PHOTOMETRIC Efficacy 86 LPW Lumens 300 lm CCT 2700 K CRI 80 CRI PMENSIONS MOL 4.6 in SATINGS & CERTIFICATIONS Safety Certifications Use NSF Rated No Location Ratings Damp PACKAGING INFO Standard Pack Quantity 12	Wattage		3.5 W
Dimmable Operating Temp Operating Temp Warranty Operating Temp Ope	Wattage Replacement		40
Operating Temp Warranty PHOTOMETRIC Efficacy Lumens 300 Im CCT 2700 K CRI RATINGS & CERTIFICATIONS Safety Certifications NSF Rated Lucation Ratings ACKAGING INFO Standard Pack Quantity -20 to 40 °C 3 year limited warranty 4 Lucation Ratings -20 to 40 °C 3 year limited warranty 3 year limited warranty 3 year limited warranty 4 Lucation Ratings -20 to 40 °C 3 year limited warranty -20 to 40 °C -20	Operating Life		15,000 hr
Werranty PHOTOMETRIC Efficacy 86 LPW Lumens 300 lm CCT 2700 K CRI 80 CRI FINANCIA 80 CRI	Dimmable		Yes
PHOTOMETRIC Efficacy 86 LPW Lumens 300 Im CCT 2700 K CRI 80 CRI MOL 4.6 in TATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated No Location Ratings No ACKAGING INFO Standard Pack Quantity 12	Operating Temp		-20 to 40 °C
Efficacy 86 LPW Lumens 300 lm CCT 2700 K CRI 80 CRI MOL 4.6 in ***********************************	Warranty		3 year limited warranty
Efficacy 86 LPW Lumens 300 lm CCT 2700 K CRI 80 CRI MOL 4.6 in ***********************************	PHOTOMETRIC		
CCT 2700 K CRI 80 CRI MOL 4.6 in CATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated No No Damp PACKAGING INFO Standard Pack Quantity 12	Efficacy	86 LPW	
CRI 80 CRI DIMENSIONS MOL 4.6 in CATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated No Location Ratings Damp PACKAGING INFO Standard Pack Quantity 12	Lumens	300 lm	
MOL 4.6 in RATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated No Location Ratings Damp PACKAGING INFO Standard Pack Quantity 12	ССТ	2700 K	
MOL 4.6 in ATTINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated Location Ratings PACKAGING INFO Standard Pack Quantity 4.6 in 12	CRI	80 CRI	
MOL 4.6 in ATTINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated Location Ratings PACKAGING INFO Standard Pack Quantity 4.6 in 12	DIMENSIONS		
Safety Certifications NSF Rated No Location Ratings PACKAGING INFO Standard Pack Quantity CULus No Damp	MOL	4.6 in	
Safety Certifications NSF Rated No Location Ratings PACKAGING INFO Standard Pack Quantity CULus No Damp			
NSF Rated Location Ratings PACKAGING INFO Standard Pack Quantity No Damp Damp			el II
Location Ratings PACKAGING INFO Standard Pack Quantity Damp 12			
PACKAGING INFO Standard Pack Quantity 12	NSF Rated		No
Standard Pack Quantity 12	Location Ratings		Damp
	PACKAGING INFO		
UPC 662049501094	Standard Pack Quantity		12
	UPC		662049501094

 $Energy\ Star\ Certified\ models\ available.\ Please\ refer\ to\ \underline{https://www.energystar.gov/productfinder/product/certified-light-bulbs/}\ for\ complete\ information.;$

Source URL: https://www.led.com/catalog/led-candle-replacement-lamps-93142797