

## LED5DFCAC-W-2PK

LED Candle Replacement Lamps

## **SKU #** 93142801



## **SPECIFICATIONS**

Bulb Base Type       E12         Voltage       120         Wattage       5 W         Wattage Replacement       60         Operating Life       15,000 hr         Dimmable       20 to 40 °C         Operating Temp       20 to 40 °C         Warranty       3 year limited warranty         PHOTOMETRIC         Efficacy       100 LPW         Lumens       500 Im         CCT       2700 K         CRI       80 CRI         PHOTOMETRIC         CRIT         CRI       80 CRI         CRIT         CRI       80 CRI         CRIT         Safety Certifications         NS Rated       V         Location Ratings       V       D Damp         PACKAGING INFO         Standard Pack Quantity       12	GENERAL		
Voltage         120           Wattage Replacement         60           Operating Life         15,000 hr           Dimmable         Yes           Operating Temp         -20 to 40 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         100 LPW           Lumens         500 lm           CCT         2700 K           CRI         80 CRI           PHOTOMETRIC           STATINGS & CERTIFICATIONS           Safety Certifications           AL in	Bulb Shape		CA
Wattage         5 W           Wattage Replacement         60           Operating Life         15,000 hr           Dimmable         Yes           Operating Temp         -20 to 40 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         100 LPW           Lumens         500 lm           CCT         2700 K           CRI         80 CRI           PHOTOMETRIC           STATINGS & CERTIFICATIONS           CRATINGS & CERTIFICATIONS           CULus           NSF Rated         No           Location Ratings         Damp           PACKAGING INFO           Standard Pack Quantity         12	Bulb Base Type		E12
Wattage Replacement       60         Operating Life       15,000 hr         Dimmable       Yes         Operating Temp       -20 to 40 °C         Warranty       3 year limited warranty         PHOTOMETRIC         Efficacy       100 LPW         Lumens       500 lm         CCT       2700 K         CRI       80 CRI         PMENSIONS         MRATINGS & CERTIFICATIONS         Safety Certifications       4.6 in         CULus         NSF Rated       No         Location Ratings       Damp         PACKAGING INFO         Standard Pack Quantity       12	Voltage		120
Operating Life       15,000 hr         Dimmable       Yes         Operating Temp       -20 to 40 °C         Warranty       3 year limited warranty         PHOTOMETRIC         Efficacy       100 LPW         Lumens       500 lm         CCT       2700 K         CRI       80 CRI         PMENSIONS         MOL       4.6 in         Safety Certifications         Safety Certifications       ULUs         NSF Rated       No         Location Ratings       Damp         PACKAGING INFO         Standard Pack Quantity       12	Wattage		5 W
Dimmable         Yes           Operating Temp         -20 to 40 °C           Warranty         3 year limited wranty           PHOTOMETRIC           Efficacy         100 LPW           Lumens         500 Im           CCT         2700 K           CRI         80 CRI           PHOTOMETRIC           MOL         4.6 in           Safety Certifications           NSF Rated         -         No           Location Ratings         -         Damp           PACKAGING INFO         -         12	Wattage Replacement		60
Operating Temp       -20 to 40 °C         Warranty       3 year limited warranty         PHOTOMETRIC         Efficacy       100 LPW         Lumens       500 Im         CCT       2700 K         CRI       80 CRI         PMOL       4.6 in         RATINGS & CERTIFICATIONS         Safety Certifications       CULUS         NSF Rated       No         Location Ratings       Damp         PACKAGING INFO       12	Operating Life		15,000 hr
Warranty  PHOTOMETRIC  Efficacy  Lumens  500 lm  CCT  2700 K  CRI  80 CRI  PINATIONS  MOL  ALGERIA CERTIFICATIONS  Safety Certifications  NSF Rated  Location Ratings  NSF Rated  Location Ratings  ALGERIA COULUS  NSF Rated  Location Ratings  Safety Certifications  NO  Location Ratings  ALGERIA COULUS  NO  Damp  PACKAGING INFO  Standard Pack Quantity	Dimmable		Yes
PHOTOMETRIC  Efficacy 100 LPW Lumens 500 Im  CCT 2700 K CRI 80 CRI  PMOL 4.6 in  RATINGS & CERTIFICATIONS  Safety Certifications CULus NSF Rated VILUS NSF Rat	Operating Temp		-20 to 40 °C
Efficacy 100 LPW  Lumens 500 lm  CCT 2700 K  CRI 80 CRI  MOL 4.6 in  RATINGS & CERTIFICATIONS  Safety Certifications ULus NSF Rated No Location Ratings No  PACKAGING INFO  Standard Pack Quantity 12	Warranty		3 year limited warranty
Efficacy 100 LPW  Lumens 500 lm  CCT 2700 K  CRI 80 CRI  MOL 4.6 in  RATINGS & CERTIFICATIONS  Safety Certifications ULus NSF Rated No Location Ratings No  PACKAGING INFO  Standard Pack Quantity 12	PHOTOMETRIC		
CCT 2700 K CRI 80 CRI  DIMENSIONS  MOL 4.6 in  RATINGS & CERTIFICATIONS  Safety Certifications CULus NSF Rated No Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 12	Efficacy	100 LPW	
MOL 4.6 in  RATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated No Location Ratings Damp  PACKAGING INFO Standard Pack Quantity 12	Lumens	500 lm	
MOL 4.6 in  RATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated No Location Ratings Damp  PACKAGING INFO Standard Pack Quantity 12	ССТ	2700 K	
MOL 4.6 in  RATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated Location Ratings PACKAGING INFO Standard Pack Quantity  4.6 in  CULus No Damp  12	CRI	80 CRI	
MOL 4.6 in  RATINGS & CERTIFICATIONS Safety Certifications CULus NSF Rated Location Ratings PACKAGING INFO Standard Pack Quantity  4.6 in  CULus No Damp  12	DIMENSIONS		
Safety Certifications  NSF Rated No Location Ratings  PACKAGING INFO  Standard Pack Quantity  CULus  No Domp  12	MOL	4.6 in	
Safety Certifications  NSF Rated No Location Ratings  PACKAGING INFO  Standard Pack Quantity  CULus  No Domp  12	RATINGS & CERTIFICATIONS		
Location Ratings  PACKAGING INFO Standard Pack Quantity  Damp  12	Safety Certifications		cULus
PACKAGING INFO Standard Pack Quantity  12	NSF Rated		No
Standard Pack Quantity 12	Location Ratings		Damp
Standard Pack Quantity 12	PACKAGING INFO		
UPC 662049501131	Standard Pack Quantity		12
	UPC		662049501131

 $Energy\ Star\ Certified\ models\ available.\ Please\ refer\ to\ \underline{https://www.energystar.gov/productfinder/product/certified-light-bulbs/}\ for\ complete\ information.;$ 

**Source URL:** https://www.led.com/catalog/led-candle-replacement-lamps-93142801