

LED18D38OW3840/40

LED PAR38 Replacement Lamps

SKU # 93172



SPECIFICATIONS

Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity CULus Wet Wet	GENERAL	
Valtage	Bulb Shape	PAR38
Wattage 18 W Wattage Replacement 50 C Operating Life 55,000 hr Dimmable 78 C Operating Temp 20 to 45 °C Warranty 3 year limited warranty PHOTOMETRIC Efficacy 94 LP Lumens 1,700 lr CCT 4000 k CRI 81 CRI WATTINGS CONTINUATION 5.3 in ATTINGS & CERTIFICATIONS Safety Certifications 4.88 in Location Ratings 6 CACKAGION INFO Standard Pack Quantity 6	Bulb Base Type	E26
Watage Replacement 150 Operating Life 25,000 hr Dimmable Yes Operating Temp 20 to 45 °C Warranty 3 year limited warranty PHOTOMETRIC Efficacy 94 LPW Lumens 1,700 lmm CCT 4000 k CRI 31 CRI WMOL 5.3 in Diameter 48 ST Safety Certifications 1 CULus Safety Certifications Wet PACKAGING INFO Standard Pack Quantity 6	Voltage	120
Operating Life 5.000 hr Dimmable 7es Operating Temp 20 to 45 °C Warranty 3 year limited warranty PHOTOMETRIC Efficacy 94 LPV Lumens 1,700 lm CCT 4000 k CRI 81 CRI MOL 5.3 in Diameter 5.3 in Saffety Certifications 5.3 in Saffety Certifications UULus Caction Ratings Wet PACKAGING INFO 5.3 in Saffety Certifications UULus Cutton Ratings Wet	Wattage	18 W
Dimmable Yes Operating Temp -20 to 45 °C Warranty 3 year limited warranty PHOTOMETRIC Efficacy 94 LP* Lumens 1,700 lm* CCT 4000 k CRI 81 CRI* PMENSIONS MOL 5.3 in Diameter 4.88 in Diameter 4.88 in Safety Certifications ULUs Location Ratings Wet PACKAGING INFO 5	Wattage Replacement	150
10 10 10 10 10 10 10 10	Operating Life	25,000 hr
Warranty PHOTOMETRIC Efficacy 94 LPW Lumens 1,700 Im CCT 4000 K CRI 81 CRI PHOTOMETRIC WETHER STATE STA	Dimmable	Yes
PHOTOMETRIC Efficacy 94 LPW	Operating Temp	-20 to 45 °C
Efficacy 94 LPW Lumens 1,700 lm CCT 4000 K CRI 81 CRI SA Sin Diameter 5.3 in CRATINGS & CERTIFICATIONS Safety Certifications V Location Ratings V PACKAGING INFO Standard Pack Quantity 6	Warranty	3 year limited warranty
Efficacy 94 LPW Lumens 1,700 lm CCT 4000 K CRI 81 CRI SA Sin Diameter 5.3 in CRATINGS & CERTIFICATIONS Safety Certifications V Location Ratings V PACKAGING INFO Standard Pack Quantity 6	PHOTOMETRIC	
Lumens CCT 4000 K CRI 4000 K CRI 5.3 in Diameter 4.88 in ATINGS & CERTIFICATIONS RATINGS & CERTIFICATIONS Safety Certifications UUUs Location Ratings Wet Standard Pack Quantity 6		94 LPW
DIMENSIONS MOL Diameter ATTINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 81 CRI SI CRI SI CRI SI CRI		1,700 lm
MOL 5.3 in Diameter 4.88 in RATINGS & CERTIFICATIONS Safety Certifications UULus Location Ratings Wet Standard Pack Quantity 6	CCT	4000 K
MOL Diameter ARATINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 5.3 in 5.3 in 5.3 in 5.4 Wether Standard Pack Quantity 4.88 in 5.4 Wether Standard Pack Quantity 6	CRI	81 CRI
MOL Diameter ARATINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 5.3 in 5.3 in 5.3 in 5.4 Wether Standard Pack Quantity 4.88 in 5.4 Wether Standard Pack Quantity 6		
PACKAGING INFO Standard Pack Quantity 4.88 in		E D in
RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Wet PACKAGING INFO Standard Pack Quantity 6		
Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity CULus Wet Wet	Diameter	4.88 in
Location Ratings Wet PACKAGING INFO Standard Pack Quantity 6	RATINGS & CERTIFICATIONS	
PACKAGING INFO Standard Pack Quantity 6	Safety Certifications	cULus
Standard Pack Quantity 6	Location Ratings	Wet
Standard Pack Quantity 6	PACKAGING INFO	
		6
	UPC	043168931724

Energy Star Certified models available. Please refer to https://www.energystar.gov/productfinder/product/certified-light-bulbs/ for complete information.;

Source URL: https://www.led.com/catalog/led-par38-replacement-lamps-93172