

## LED32DP38W835/40-120

LED PAR38 Lamps

## **SKU #** 30239



## **SPECIFICATIONS**

Bulb Shape       FAR38         Bulb Base Type       526         Voltage       120         Wattage Replacement       52 V9         Operating Life       55,000 hr         Operating Life       765         Operating Temp       765         Operating Temp       30 year Imited warrenty         PHOTOMETIC       310 January         Efficacy       97 LPW         CCT       300 N         CR       400 N         CR       300 N         CR       400 N         Diameter       512 N         Sefety Certifications       512 N         Creating Ratings       400 N         Creating Ratings       400 N         Creating Ratings       400 N         Creating Ratings       400 N         Creating R	GENERAL	
Voltage       120         Wattage Replacement       250         Operating Life       25,000 hr         Dimmable       720         Operating Temp       120         Warranty       20 to 45 °C         Warranty       3 year limited w=nty         Efficacy       97 LPW         Lumens       3,100 lm         CCT       3500 K         CRI       3500 K         WBMASIONS       512 lm         MOL       512 lm         Diameter       48 lm         Safety Certifications       512 lm         Sefety Certifications       512 lm         Location Ratings       510 lm         PACKAGING INFO       Wet	Bulb Shape	PAR38
Wattage       32 W         Wattage Replacement       250         Operating Life       25,000 hr         Dimmable       Yes         Operating Temp       -20 to 45 °C         Warranty       3 year limited warranty         PHOTOMETRIC         Efficacy       97 LPV         Lumens       3,100 l         CCT       80 CR         CRI       80 CR         PMENSIONS         MOL       5,12 l         Diameter       4,8 in         CRITICATIONS         Safety Certifications         CULus         ACKAGING INFO	Bulb Base Type	E26
Wattage Replacement       550         Operating Life       25,000 hr         Dimmable       Yes         Operating Temp       -20 to 45 °C         Warranty       3 year limited warnty         PHOTOMETRIC         Efficacy       97 LPW         Lumens       3,100 lm         CCT       3500 k         CRI       30 CRI         MOL       5.12 lm         Diameter       4.8 is         RATINGS & CERTIFICATIONS         Safety Certifications       1	Voltage	120
Operating Life         25,000 hr           Dimmable         Yes           Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         97 LPW           Lumens         3,100 lm           CCT         3500 K           CRI         80 CRI           PIMENSIONS           MOL         5.12 in           Diameter         4.8 in           RATINGS & CERTIFICATIONS           Safety Certifications         ULLus           Location Ratings         Wet	Wattage	32 W
Dinmable         Yes           Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         97 LPW           Lumens         3,100 Im           CCT         3500 K           CRI         80 CRI           PMOL           Diameter         5.12 in           PATINGS & CERTIFICATIONS           Safety Certifications         UULus           Location Ratings         Wet	Wattage Replacement	250
Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         97 LPW           Lumens         3,100 Im           CCT         3500 K           CRI         80 CRI           PMENSIONS           MOL         5.12 in           Diameter         4.8 in           CRITINGS & CERTIFICATIONS           Safety Certifications         CULUS           Location Ratings         Wet	Operating Life	25,000 hr
Marranty           PHOTOMETRIC           Efficacy         97 LPW	Dimmable	Yes
PHOTOMETRIC           Efficacy         97 LPW	Operating Temp	-20 to 45 °C
Efficacy       97 LPW         Lumens       3,100 lm         CCT       3500 K         CRI       80 CRI         DIMENSIONS         MOL       5.12 in         Diameter       4.8 in         RATINGS & CERTIFICATIONS         Safety Certifications       ULlus         Location Ratings       Wet         PACKAGING INFO	Warranty	3 year limited warranty
Efficacy       97 LPW         Lumens       3,100 lm         CCT       3500 K         CRI       80 CRI         DIMENSIONS         MOL       5.12 in         Diameter       4.8 in         RATINGS & CERTIFICATIONS         Safety Certifications       ULlus         Location Ratings       Wet         PACKAGING INFO	PHOTOMETRIC	
Lumens 3,100 lm  CCT 3500 K  CRI 80 CRI  MOL 5.12 in  Diameter 4.8 in  RATINGS & CERTIFICATIONS  Safety Certifications ULus Location Ratings Wet		97 LPW
CCT CRI 80 CRI  DIMENSIONS  MOL 5.12 in Diameter 4.8 in  RATINGS & CERTIFICATIONS  Safety Certifications Location Ratings  MOL  PACKAGING INFO		
DIMENSIONS  MOL 5.12 in Diameter 4.8 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Wet		
MOL 5.12 in Diameter 4.8 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Wet		
MOL 5.12 in Diameter 4.8 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Wet  PACKAGING INFO		
Diameter 4.8 in  RATINGS & CERTIFICATIONS Safety Certifications cULus Location Ratings Wet  PACKAGING INFO	DIMENSIONS	
RATINGS & CERTIFICATIONS Safety Certifications cULus Location Ratings Wet  PACKAGING INFO	MOL	5.12 in
Safety Certifications cULus Location Ratings Wet  PACKAGING INFO	Diameter	4.8 in
Location Ratings Wet  PACKAGING INFO	RATINGS & CERTIFICATIONS	
PACKAGING INFO		cULus
	Location Ratings	Wet
	PACKAGING INFO	
		6
UPC 043168302395		

 $Energy\ Star\ Certified\ models\ available.\ Please\ refer\ to\ \underline{https://www.energystar.gov/productfinder/product/certified-light-bulbs/}\ for\ complete\ information.;$ 

**Source URL:** https://www.led.com/catalog/led-par38-lamps-30239