

## LED7DP203B827/20

LED PAR20 Replacement Lamps

## **SKU #** 93349



## **SPECIFICATIONS**

MOL 3.5 in 2.48 in	GENERAL	
Voltage         120           Wattage Replacement         50           Operating Life         25,000 hr           Operating Temp         70 to 45 °C           Operating Temp         30 year limited warranty           PHOTOMETRIC           Efficacy         71 LPV           Lumens         500 hr           CCT         2700 kT           CRI         80 CRI           CRI         3.5 in           Diameter         3.5 in           Diameter         3.5 in           Safety Certifications         5 dllus           Location Ratings         5 dllus           PACKAGININFO         5 apap	Bulb Shape	PAR20
Watage Replacement         50           Operating Life         500 hr           Dimmable         49 S           Operating Temp         20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         71 LPW           Lumens         200 hr           CCT         270 k           CRI         30 cRI           WBMSIONS         3.5 in           MOL         3.5 in           Diameter         3.4 in           Safety Certifications         2.48 in           Location Ratings         5 ULus           PACKAGING INFO           Standard Pack Quantity         6	Bulb Base Type	E26
Matage Replacement	Voltage	120
Operating Life         25,000 hr           Dimmable         Yes           Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         71 LPW           Lumens         500 lm           CCT         2700 k           CRI         30 CRI           MOL         3.5 in           Diameter         3.5 in           Sefety Certifications         2.48 in           Safety Certifications         ULUs           Location Ratings         Damp           PACKAGING INFO         5           Standard Pack Quantity         6	Wattage	7 W
Dimmable         Yes           Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         71 LPW           Lumens         500 Im           CCT         2700 K           CRI         80 CRI           PMENSIONS           MOL         3.5 in           Diameter         2.48 in           CULus           ATRINGS & CERTIFICATIONS         ULLus           Safety Certifications         ULLus           Location Ratings         Damp           PACKAGING INFO         5	Wattage Replacement	50
Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         71 LPW           Lumens         500 lm           CCT         2700 k           CRI         80 CRI           PMENSIONS           MOL         3.5 in           Diameter         3.5 in           Diameter         2.48 in           CULus           Location Ratings         CULus           Damp           PACKAGING INFO           Standard Pack Quantity         6	Operating Life	25,000 hr
PHOTOMETRIC  Efficacy 71 LPW Lumens 500 Im  CCT 2700 K CRI 80 CRI  DIMENSIONS  MOL 3.5 in Diameter 2.48 in  FATINGS & CERTIFICATIONS  Safety Certifications cUlus Location Ratings  Clus  PACKAGING INFO  Standard Pack Quantity 6	Dimmable	Yes
PHOTOMETRIC  Efficacy	Operating Temp	-20 to 45 °C
Efficacy       71 LPW         Lumens       500 lm         CCT       2700 k         CRI       80 CRI         MOL         Diameter       3.5 in         CRATINGS & CERTIFICATIONS         Safety Certifications       3.48 in         Location Ratings       ULus         Damp         PACKAGING INFO         Standard Pack Quantity       6	Warranty	3 year limited warranty
Efficacy       71 LPW         Lumens       500 lm         CCT       2700 k         CRI       80 CRI         MOL         Diameter       3.5 in         CRATINGS & CERTIFICATIONS         Safety Certifications       3.48 in         Location Ratings       ULus         Damp         PACKAGING INFO         Standard Pack Quantity       6	PHOTOMETRIC	
Lumens CCT CCT  CRI  80 CRI  MOL Diameter  MOL Diameter  2.48 in  CRI  ATINGS & CERTIFICATIONS  ACTIVE ACTI		71 I PW
CCT CRI 2700 K  CRI 80 CRI  MOL 3.5 in Diameter 2.48 in  CATINGS & CERTIFICATIONS  Safety Certifications UULus Location Ratings UDAMP  PACKAGING INFO  Standard Pack Quantity 6		
DIMENSIONS  MOL 3.5 in Diameter 2.48 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6		
MOL 3.5 in Diameter 2.48 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6		
MOL 3.5 in Diameter 2.48 in  RATINGS & CERTIFICATIONS  Safety Certifications CULus Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6		
PACKAGING INFO Standard Pack Quantity  2.48 in  4.40 in  5.40 in  6.40 in	DIMENSIONS	
RATINGS & CERTIFICATIONS  Safety Certifications	MOL	3.5 in
Safety Certifications Location Ratings  PACKAGING INFO Standard Pack Quantity  CULus Damp  6	Diameter	2.48 in
Location Ratings  PACKAGING INFO Standard Pack Quantity  Damp  6	RATINGS & CERTIFICATIONS	
PACKAGING INFO Standard Pack Quantity 6	Safety Certifications	cULus
Standard Pack Quantity 6	Location Ratings	Damp
Standard Pack Quantity 6	PACKAGING INFO	
		6

 $Energy \ Star \ Certified \ models \ available. \ Please \ refer \ to \ \underline{https://www.energystar.gov/productfinder/product/certified-light-bulbs/} \ for \ complete \ information.;$ 

**Source URL:** https://www.led.com/catalog/led-par20-replacement-lamps-93349