

## LED7DP203B830/20

LED PAR20 Replacement Lamps

## **SKU #** 93327



## **SPECIFICATIONS**

MOL 3.5 in 2.48 in	GENERAL	
Voltage         120           Wattage Replacement         50           Operating Life         25,000 hr           Operating Temp         720 to 45 °C           Operating Temp         39 year limited warranty           PHOTOMETRIC           Efficacy         74 LPV           Lumens         520 lm           CCT         3000 k           CRI         3000 k           CRI         35 in           Diameter         3.5 in           Diameter         3.5 in           Safety Certifications         5 dllus           Location Ratings         5 dllus           PACKAGININFO         5 apap	Bulb Shape	PAR20
Watage Replacement         50           Operating Life         500 hr           Dimmable         42 kg           Operating Temp         20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         74 LPW           Lumens         520 lm           CCT         3000 k           CRI         30 kg           WBMENSIONS         3.5 in           MOL         3.5 in           Diameter         3.4 kg           Safety Certifications         2.48 kg           Location Ratings         5 ULus           PACKAGING INFO           Standard Pack Quantity         6	Bulb Base Type	E26
Natage Replacement Operating Life Operating Life Dimmable Operating Temp Operati	Voltage	120
Operating Life         25,000 hr           Dimmable         Yes           Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         74 LPW           Lumens         520 lm           CCT         3000 k           CRI         30 0 k           VINIONESONS         3.5 in           Diameter         3.5 in           Diameter         3.5 in           Sefety Certifications         ULUs           Location Ratings         Damp           PACKAGING INFO         5	Wattage	7 W
Dimmable         Yes           Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         74 LPW           Lumens         520 Im           CCT         3000 K           CRI         80 CRI           PMENSIONS           MOL         3.5 in           Diameter         2.48 in           CULus           ATHINGS & CERTIFICATIONS         ULLus           Safety Certifications         ULLus           Location Ratings         Damp           PACKAGING INFO         6	Wattage Replacement	50
Operating Temp         -20 to 45 °C           Warranty         3 year limited warranty           PHOTOMETRIC           Efficacy         74 LPW           Lumens         520 lm           CCT         3000 k           CRI         80 CRI           PMENSIONS           MOL         3.5 in           Diameter         3.5 in           Diameter         2.48 in           CULus           Location Ratings         CULus           PACKAGING INFO           Standard Pack Quantity         6	Operating Life	25,000 hr
PHOTOMETRIC  Efficacy 74 LPW Lumens 520 Im  CCT 3000 K CRI 3000 K CRI 30.5 IM  MOL 3.5 IM Diameter 2.48 IM  FATINGS & CERTIFICATIONS  Safety Certifications CULUS Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6	Dimmable	Yes
PHOTOMETRIC  Efficacy 74 LP  Lumens 520   CCT 3000   CRI 80 CR  PMOL 51    MOL 51    MOL 51    MOL 51    MOL 52	Operating Temp	-20 to 45 °C
Efficacy       74 LPW         Lumens       520 lm         CCT       3000 k         CRI       80 CRI         DIMENSIONS         MOL       3.5 in         Diameter       2.48 in         CRATINGS & CERTIFICATIONS         Safety Certifications       ULUs         Location Ratings       Damp         PACKAGING INFO         Standard Pack Quantity       6	Warranty	3 year limited warranty
Efficacy       74 LPW         Lumens       520 lm         CCT       3000 k         CRI       80 CRI         DIMENSIONS         MOL       3.5 in         Diameter       2.48 in         CRATINGS & CERTIFICATIONS         Safety Certifications       ULUs         Location Ratings       Damp         PACKAGING INFO         Standard Pack Quantity       6	PHOTOMETRIC	
Lumens CCT  CCT  CRI  80 CRI  MOL  Diameter  MOL  Diameter  2.48 in  CRI  Safety Certifications  Location Ratings  PACKAGING INFO  Standard Pack Quantity  520 Im  520		74 I PW
CCT CRI  80 CRI  MOL Diameter  8.5 in 2.48 in  RATINGS & CERTIFICATIONS  Safety Certifications Location Ratings  PACKAGING INFO  Standard Pack Quantity  3000 K  1000		
DIMENSIONS  MOL 3.5 in Diameter 2.48 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6		
MOL 3.5 in Diameter 2.48 in  RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6		
MOL 3.5 in Diameter 2.48 in  RATINGS & CERTIFICATIONS  Safety Certifications CULus Location Ratings Damp  PACKAGING INFO  Standard Pack Quantity 6		
PACKAGING INFO Standard Pack Quantity  2.48 in  4.40 in  5.40 in  6.40 in	DIMENSIONS	
RATINGS & CERTIFICATIONS  Safety Certifications	MOL	3.5 in
Safety Certifications Location Ratings  PACKAGING INFO Standard Pack Quantity  CULus Damp  6	Diameter	2.48 in
Location Ratings  PACKAGING INFO Standard Pack Quantity  Damp  6	RATINGS & CERTIFICATIONS	
PACKAGING INFO Standard Pack Quantity 6	Safety Certifications	cULus
Standard Pack Quantity 6	Location Ratings	Damp
Standard Pack Quantity 6	PACKAGING INFO	
		6

 $Energy \ Star \ Certified \ models \ available. \ Please \ refer \ to \ \underline{https://www.energystar.gov/productfinder/product/certified-light-bulbs/} \ for \ complete \ information.;$ 

**Source URL:** https://www.led.com/catalog/led-par20-replacement-lamps-93327