

LED11BDT5/G2/830

LED Type B Double Ended T5 Glass Tubes

SKU # 93113793



SPECIFICATIONS

Safety Certifications cULus Location Ratings Damp	GENERAL	
Bib Base Type Voltage Voltag	UL Type	Туре В
Voltage 120-277 Wattage Replacement 11 W Operating Life 50.000 hr Operating Temp 10 V Operating Temp 20 to 45 °C Warranty PHOTOMETRIC Efficacy 136 LPW CCT 3000 K CRI 3000 K <t< td=""><td>Bulb Shape</td><td>Т5</td></t<>	Bulb Shape	Т5
Watage Replacement 1 M Operating Life 50,000 hr Dimmable 70,000 hr Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 1,500 lm CCT 3000 K CRI 80 CRI VARIANCE 80 CRI VARIANCE CERTIFICATIONS Safety Certifications Location Ratings ULUS PACKAGING INFO 20 m Landard Pack Quantity 20 m	Bulb Base Type	G5
Watage Replacement MA Operating Life 50,000 hr Dimmable No Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 136 LPW Lumens 1,500 lm CCT 3000 k CRI 3000 k PHOTOMETRIC MOL 20 lm CRI 3000 k CRI 0.63 lm Diameter 0.63 lm PACKAGING INFO Sately Certifications 10 lm CACKAGING INFO 10 lm	Voltage	120-277
Operating Life 50,000 hr Dimmable No Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 136 LPW Lumens 1,500 Im CCT 3000 K CRI 80 CRI PMENSIONS Safety Certifications Safety Certifications Safety Certifications Safety Certifications ULUs Doamp PACKAGING INFO Standard Pack Quantity 20	Wattage	11 W
Dimmable 0perating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 136 LP	Wattage Replacement	N/A
Operating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 136 LPW Lumens 1,500 Im CCT 3000 K CRI 3000 K POMENSIONS MOL 22 in Diameter 0.63 in Diameter 0.63 in Safety Certifications CULus Location Ratings Damp PACKAGING INFO 30 Standard Pack Quantity 20	Operating Life	50,000 hr
PHOTOMETRIC Efficacy 136 LPW	Dimmable	No
PHOTOMETRIC Efficacy 136 LPW Lemens 1,500 lm Lemens Lemens 1,500 lm Lemens Lemens 1,500 lm Lemens Lemens <td>Operating Temp</td> <td>-20 to 45 °C</td>	Operating Temp	-20 to 45 °C
Efficacy 136 LPW Lumens 1,500 lm CCT 3000 K CRI 80 CRI DIMENSIONS MOL 22 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications	Warranty	5 year limited warranty
Efficacy 136 LPW Lumens 1,500 lm CCT 3000 K CRI 80 CRI DIMENSIONS MOL 22 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications	PHOTOMETRIC	
CCT 200 3000 K CRI 3000 K DIMENSIONS MOL 22 in Diameter 20.63 in RATINGS & CERTIFICATIONS Safety Certifications UULus Location Ratings UDAGAGING INFO Standard Pack Quantity 20		136 LPW
DIMENSIONS MOL 22 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	Lumens	1,500 lm
MOL 22 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	ССТ	3000 K
MOL 22 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	CRI	80 CRI
MOL 22 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	DIMENSIONS	
RATINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 20		22 in
Safety Certifications cULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	Diameter	0.63 in
Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	RATINGS & CERTIFICATIONS	
PACKAGING INFO Standard Pack Quantity 20	Safety Certifications	cULus
Standard Pack Quantity 20	Location Ratings	Damp
	PACKAGING INFO	
UPC 043168507783	Standard Pack Quantity	20
	UPC	043168507783

 $\textbf{Source URL:} \ https://www.led.com/catalog/led-type-b-double-ended-t5-glass-tubes-93113793$