

LED17BDT5/G3/840

LED Type B Double Ended T5 Glass Tubes

SKU # 93114629G



SPECIFICATIONS

ULType Bulb Shape Bulb Shape Voltage Voltage Voltage Voltage Voltage Voltage Peplacement Voltage Peplacement Voltage Voltage Replacement Voltage Voltage Peplacement Voltage Peplacemen	GENERAL		
Bilb Base Type 55 Voltage 120-277 Wattage 17 W Wattage Replacement NA Operating Life 50,000 hr Dimmable 20 to 45 °C Operating Temp 20 to 45 °C Warranty 147 LPW Efficacy 147 LPW Lumens 2500 Imr CCT 4000 K CRI 80 CRI MEMENSIONS 30 A Imr MINENSIONS 34 Imr Safety Certifications 400 A Imr Barrings & CERTIFICATIONS 400 M Imr Safety Certifications 400 M Imr	UL Type	Туре В	
Voltage 120-277 Wattage Replacement 17 W Operating Life 50,000 hr Dimmable 80 Operating Temp 20 to 45 °C Warranty 5 year limited wranty PHOTOMETRIC Efficacy 147 LPW Lumens 2,500 lm CCT 4000 K CRI 80 CRI Diameter 90 CRI MOL 34 in Diameter 90.63 in PATINGS & CERTIFICATIONS ULUs Safety Certifications ULUs Location Ratings 0 Jamp PACKAGING INFO 30 mg	Bulb Shape	T5	
Watage Replacement 17 W Operating Life 50,000 hr Operating Temp 10 e Warranty 20 to 45 °C FMOTOMETRIC Efficacy 147 LPW Lumens 2,500 Im CCT 4000 K CRI 80 CRI FMENSIONS MOL 90 CRI Diameter 9 d is 1 Patrings & CERTIFICATIONS ULUS Safety Certifications ULUS Location Ratings 20 mp	Bulb Base Type	G5	
Wattage Replacement NA Operating Life 50,000 hr Dimmable No Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 147 LPW Lumens 2,500 lm CCT 4000 K CRI 80 CRI PMENSIONS RATINGS CERTIFICATIONS Safety Certifications 34 in Safety Certifications ULUs Location Ratings Damp PACKAGING INFO 320	Voltage	120-277	
Operating Life 50,000 hr Dimmable No Operating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 147 LPW Lumens 2,500 lm CCT 4000 K CRI 80 CRI PMENSIONS ATMINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings CULus Damp PACKAGING INFO Standard Pack Quantity	Wattage	17 W	
Dinmable No Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 147 LPW Lumens 2,500 Im CCT 4000 K CRI 80 CRI PMENSIONS MOL 34 im Diameter 0.63 im Packaging Experimental Location Ratings CULlus Location Ratings Damp PACKAGING INFO 20	Wattage Replacement	N/A	
Operating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 147 LPW Lumens 2,500 lm CCT 4000 K CRI 80 CRI PMENSIONS A 4 in Included the property of th	Operating Life	50,000 hr	
PHOTOMETRIC Efficacy 147 LPW Lumens 2,500 Im CCT 4000 K CRI 4000 K CRI 30 CRI MOL 34 Im Diameter 0,603 Im RATINGS & CERTIFICATIONS RATINGS & CERTIFICATIONS Safety Certifications UULus Location Ratings UULus Location Ratings 20 PACKAGING INFO Standard Pack Quantity 20	Dimmable	No	
PHOTOMETRIC Efficacy 147 LPW	Operating Temp	-20 to 45 °C	
Efficacy 147 LPW Lumens 2,500 lm CCT 4000 K CRI 80 CRI DIMENSIONS MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications ULUs Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	Warranty	5 year limited warranty	
Efficacy 147 LPW Lumens 2,500 lm CCT 4000 K CRI 80 CRI DIMENSIONS MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications ULUs Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	PHOTOMETRIC		
CCT 4000 K CRI 80 CRI MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications UULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20		147 LPW	
DIMENSIONS MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	Lumens	2,500 lm	
MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	ССТ	4000 K	
MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	CRI	80 CRI	
MOL 34 in Diameter 0.63 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	DIMENSIONS		
RATINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 20	MOL	34 in	
Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 20	Diameter	0.63 in	
Location Ratings PACKAGING INFO Standard Pack Quantity Damp 20	RATINGS & CERTIFICATIONS		
PACKAGING INFO Standard Pack Quantity 20	Safety Certifications	cULus	
Standard Pack Quantity 20	Location Ratings	Damp	
	PACKAGING INFO		
UPC 043168508162	Standard Pack Quantity	20	
	UPC	043168508162	

 $\textbf{Source URL:} \ https://www.led.com/catalog/led-type-b-double-ended-t5-glass-tubes-93114629G$